

# VRT-SERIES Inline shaft

## VRT-064 – 1-Stage Specifications

Frame Size	064									
Stage	1-Stage									
Ratio	Unit	Note	4	5	6	7	8	9	10	
Nominal Output Torque	[Nm]	*1	27	27	27	27	27	18	18	
Maximum Acceleration Torque	[Nm]	*2	50	50	50	50	50	35	35	
Emergency Stop Torque	[Nm]	*3	100	100	100	100	100	80	80	
Nominal Input Speed	[rpm]	*4				3000				
Maximum Input Speed	[rpm]	*5				6000				
No Load Running Torque	[Nm]	*6				0.08				
Permitted Radial Load	[N]	*7	370	400	420	440	460	480	500	
Permitted Axial Load	[N]	*8	360	390	430	460	480	510	530	
Maximum Radial Load	[N]	*9				1500				
Maximum Axial Load	[N]	*10				750				
Moment of Inertia ( $\leq \varnothing 8$ )	[kgcm <sup>2</sup> ]	--	0.130	0.100	0.085	0.075	0.068	0.064	0.062	
Moment of Inertia ( $\leq \varnothing 14$ )	[kgcm <sup>2</sup> ]	--	0.210	0.180	0.170	0.150	0.150	0.140	0.140	
Moment of Inertia ( $\leq \varnothing 19$ )	[kgcm <sup>2</sup> ]	--	0.400	0.400	0.400	0.400	0.400	0.400	0.400	
Efficiency	[%]	*11				95				
Torsional Rigidity	[Nm/arc-min]	*12				3				
Maximum Torsional Backlash	[arc-min]	--				$\leq 3$				
Noise Level	[dB]	*13				$\leq 66$				
Protection Class	--	*14				IP54 (IP65)				
Ambient Temperature	[°C]	--				0 - 40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*15				1.4				

## VRT-064 – 2-Stage Specifications

Frame Size	064									
Stage	2-Stage									
Ratio	Unit	Note	16	20	25	28	35	40	45	
Nominal Output Torque	[Nm]	*1	27	27	27	27	27	27	27	18
Maximum Acceleration Torque	[Nm]	*2	50	50	50	50	50	50	50	35
Emergency Stop Torque	[Nm]	*3	100	100	100	100	100	100	100	80
Nominal Input Speed	[rpm]	*4				3000				
Maximum Input Speed	[rpm]	*5				6000				
No Load Running Torque	[Nm]	*6				0.04				
Permitted Radial Load	[N]	*7	580	630	680	700	760	790	820	
Permitted Axial Load	[N]	*8	650	720	750	750	750	750	750	
Maximum Radial Load	[N]	*9				1500				
Maximum Axial Load	[N]	*10				750				
Moment of Inertia ( $\leq \varnothing 8$ )	[kgcm <sup>2</sup> ]	--	0.059	0.055	0.054	0.056	0.053	0.049	0.0530	
Moment of Inertia ( $\leq \varnothing 14$ )	[kgcm <sup>2</sup> ]	--	0.140	0.140	0.130	0.140	0.130	0.130	0.130	
Moment of Inertia ( $\leq \varnothing 19$ )	[kgcm <sup>2</sup> ]	--	0.360	0.350	0.350	0.360	0.350	0.340	0.350	
Efficiency	[%]	*11				90				
Torsional Rigidity	[Nm/arc-min]	*12				3				
Maximum Torsional Backlash	[arc-min]	--				$\leq 3$				
Noise Level	[dB]	*13				$\leq 66$				
Protection Class	--	*14				IP54 (IP65)				
Ambient Temperature	[°C]	--				0 - 40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*15				1.6				

## VRT-064 – 2-Stage Specifications

Frame Size	064							
Stage	2-Stage							
Ratio	Unit	Note	50	60	70	80	90	100
Nominal Output Torque	[Nm]	*1	27	27	27	27	18	18
Maximum Acceleration Torque	[Nm]	*2	50	50	50	50	35	35
Emergency Stop Torque	[Nm]	*3	100	100	100	100	80	80
Nominal Input Speed	[rpm]	*4			3000			
Maximum Input Speed	[rpm]	*5			6000			
No Load Running Torque	[Nm]	*6			0.04			
Permitted Radial Load	[N]	*7	850	910	950	1000	1000	1100
Permitted Axial Load	[N]	*8	750	750	750	750	750	750
Maximum Radial Load	[N]	*9			1500			
Maximum Axial Load	[N]	*10			750			
Moment of Inertia ( $\leq \emptyset 8$ )	[kgcm <sup>2</sup> ]	--	0.049	0.049	0.049	0.049	0.049	0.049
Moment of Inertia ( $\leq \emptyset 14$ )	[kgcm <sup>2</sup> ]	--	0.130	0.130	0.130	0.130	0.130	0.130
Moment of Inertia ( $\leq \emptyset 19$ )	[kgcm <sup>2</sup> ]	--	0.340	0.340	0.340	0.340	0.340	0.340
Efficiency	[%]	*11			90			
Torsional Rigidity	[Nm/arc-min]	*12			3			
Maximum Torsional Backlash	[arc-min]	--			$\leq 3$			
Noise Level	[dB]	*13			$\leq 66$			
Protection Class	--	*14			IP54 (IP65)			
Ambient Temperature	[°C]	--			0 - 40			
Permitted Housing Temperature	[°C]	--			90			
Weight	[kg]	*15			1.6			

- \*1) At nominal input speed, service life is 20,000 hours
- \*2) The maximum torque when starting or stopping operation
- \*3) The maximum torque allowed under a stress situation (Permitted 1,000 times during service life)
- \*4) The average input speed
- \*5) The maximum intermittent input speed
- \*6) This is the torque at no load applied on the input shaft. The input speed is 3,000 rpm for VRT 064
- \*7) At this load and nominal input speed, service life will be 20,000 hours. (The radial load applied to the output side bearing)
- \*8) At this load and nominal input speed, service life will be 20,000 hours. (The axial load applied to the output flange center)
- \*9) The maximum radial load that the reducer can accept
- \*10) The maximum axial load that the reducer can accept
- \*11) The efficiency at the nominal torque rating
- \*12) This does not include the lost motion
- \*13) Contact NIDEC-SHIMPO for the testing conditions and environment
- \*14) IP65 (wash-down) is available as an option. Contact NIDEC-SHIMPO for more details and our food grade options
- \*15) The weight may vary slightly between models