

EJP SERIES Right-angle Worm

EJP 038 1-Stage Specifications

Frame Size	038									
Stage	1-Stage									
Ratio	Unit	Note	5	6	7	8	9	10	15	
Nominal Output Torque	[Nm]	--	35	---	---	---	---	46	49	
Maximum Acceleration Torque	[Nm]	--	46	---	---	---	---	59	61	
Emergency Stop Torque	[Nm]	--	105	---	---	---	---	138	147	
No Load Running Torque	[Nm]	*1			0.51					
Nominal Input Speed	[rpm]	--			2,000					
Maximum Continuous Input Speed	[rpm]	--			4,000					
Maximum Cyclic Input Speed	[rpm]	--			6,000					
Maximum Radial Load	[N]	*2			3,110					
Maximum Axial Load	[N]	*3			1,780					
Moment of Inertia ($\leq \varnothing 14$)	[kgcm ²]	--	0.75	---	---	---	---	0.59	0.56	
Moment of Inertia ($\leq \varnothing 19$)	[kgcm ²]	--	0.95	---	---	---	---	0.79	0.76	
Moment of Inertia ($\leq \varnothing 28$)	[kgcm ²]	--	2.13	---	---	---	---	1.97	1.94	
Efficiency	[%]	*4	88	---	---	---	---	86	84	
Torsional Rigidity	[Nm/arcmin]	--			3.8					
Maximum Torsional Backlash (Standard)	[Arc-min]	--			≤ 24					
Maximum Torsional Backlash (Low)	[Arc-min]	--			≤ 8					
Maximum Torsional Backlash (Zero)	[Arc-min]	--			$\leq \text{---}$					
Noise Level	[dBA]	*5			≤ 73					
Ambient Temperature	[°C]	--			-25 ~ 100					
Permitted Housing Temperature	[°C]	--			100					
Protection Class	--	--			IP65					
Lubrication	--	--			Synthetic Oil					
Service Life	[Hours]	--			25,000					
Weight	[kg]	*6			4.1					

*1) Torque at no load applied to the input shaft at 2,000 rpm

*2) The maximum radial load the gearbox can accept

*3) The maximum axial load the gearbox can accept

*4) The efficiency at the nominal output torque rating

*5) Measured with no load applied to the input shaft at 2,000 rpm

*6) Weight may vary slightly between models

EJP 038 1-Stage Specifications

Frame Size	038							
Stage	1-Stage							
Ratio	Unit	Note	20	25	30	40	50	60
Nominal Output Torque	[Nm]	--	47	---	46	42	42	38
Maximum Acceleration Torque	[Nm]	--	60	---	56	52	52	47
Emergency Stop Torque	[Nm]	--	141	---	138	126	126	114
No Load Running Torque	[Nm]	*1			0.51			
Nominal Input Speed	[rpm]	--			2,000			
Maximum Continuous Input Speed	[rpm]	--			4,000			
Maximum Cyclic Input Speed	[rpm]	--			6,000			
Maximum Radial Load	[N]	*2			3,110			
Maximum Axial Load	[N]	*3			1,780			
Moment of Inertia ($\leq \varnothing 14$)	[kgcm ²]	--	0.54	---	0.54	0.53	0.53	0.53
Moment of Inertia ($\leq \varnothing 19$)	[kgcm ²]	--	0.74	---	0.74	0.73	0.73	0.73
Moment of Inertia ($\leq \varnothing 28$)	[kgcm ²]	--	1.92	---	1.92	1.91	1.91	1.91
Efficiency	[%]	*4	81	---	76	72	69	66
Torsional Rigidity	[Nm/arcmin]	--			3.8			
Maximum Torsional Backlash (Standard)	[Arc-min]	--			≤ 24			
Maximum Torsional Backlash (Low)	[Arc-min]	--			≤ 8			
Maximum Torsional Backlash (Zero)	[Arc-min]	--			$\leq ---$			
Noise Level	[dBA]	*5			≤ 73			
Ambient Temperature	[°C]	--			-25 ~ 100			
Permitted Housing Temperature	[°C]	--			100			
Protection Class	--	--			IP65			
Lubrication	--	--			Synthetic Oil			
Service Life	[Hours]	--			25,000			
Weight	[kg]	*6			4.1			

*1) Torque at no load applied to the input shaft at 2,000 rpm

*2) The maximum radial load the gearbox can accept

*3) The maximum axial load the gearbox can accept

*4) The efficiency at the nominal output torque rating

*5) Measured with no load applied to the input shaft at 2,000 rpm

*6) Weight may vary slightly between models